ShoPro® Series

Level Display | Controller



- NEMA 4X Enclosure
- **⊘** New Easy-Learn® Programming





Product Description

The **ShoPro® Series** Level Display | Controller is the industry's most rugged and reliable wall-mount remote display.

The **ShoPro**® comes as a complete all-in-one unit, out of the box it is ready to use. Included is a bright LED Display, NEMA 4X Enclosure, Polycarbonate Faceplate, Cord Grips and Plastic Captive Screws.

The industrial design ensures that it will withstand the industry's most corrosive environments. Available with Two 5A Relay + 4-20mA Output




Features

- SunBright Technology for Outdoor Applications
- No Assembly Required
- **2** Wire Cord Grips No Tools Required

Fill Pipe Clamp - No Drilling



Working Principle





Technical Specifications

General		
Display	LED 5 x 13mm High Red	
Displayed Values	-99999 ± 99999	
Stability	50 ppm °C	
Transmission Parameters	1200115200 bit/s, 8N1 / 8N2	
Protection Class	NEMA 4X IP67	
Input Signal Supply		
Standard	Current : 4-20mA	
Voltage	85 - 260V AC/DC 16 - 35V AC, 19 - 50V DC*	
Output Signal Supply		
Standard	2 x Relays 5A +4-20mA	
Voltage	24 VDC	
Passive Current Output*	4-20mA (Operating Range Max. 2.8 - 24mA)	
Performance		
Accuracy	0.1% @ 25°C One Digit	
Accuracy According to IEC 60770 - Limit Point Adjustment Non-Linearity Hysteresis Repeatability		
Temperatures		
Operating Temperatures	-40 - 158°F -40 - 70°C	
Materials		
Housing	ABS Polycarbonate	

Model Selection

Part Number	Input	Output
SP100	1 x 4-20mA	1 x 2 Relay + 4-20mA
SP200	1 x 4-20mA	2 x 2 Relay + 4-20mA
SP300	1 x 4-20mA	3 x 2 Relay + 4-20mA
SP400	1 x 4-20mA	4 x 2 Relay + 4-20mA





^{*}Contact Factory for Different Options