


LevelPro® — 250B Series

Battery Powered Liquid Level Display

ICON™ Corrosion-Free
PROCESS CONTROLS Instrumentation Equipment™




Chameleon Color Display
Outdoor Visibility Display Automatically
Changes from **Blue** to **Green**



LevelPro® — 250B Series

Battery Powered Liquid Level Display



Features

- ✓ Battery Powered
- ✓ Super Bright 4 Digit LCD Display
- ✓ Chameleon Color Display
- ✓ 4-20mA Input
- ✓ Latching (std.) or Momentary ON/OFF Switch
- ✓ NEMA 4X Enclosure
- ✓ All Plastic - Corrosion Resistant
- ✓ All Cord Grips Included
- ✓ Simple Programming

The LevelPro® level process displays and controllers are the industry's most rugged and reliable wall-mount remote level displays.

The LevelPro® 250B Series level process display and controller is the industry's most rugged and reliable wall-mount remote level display.

LevelPro® 250B Series comes as a complete all-in-one unit, out of the box it is ready to use. Included is a vivid LCD display, NEMA 4X enclosure, polycarbonate faceplate, cord grips and plastic captive screws.

The industrial design of the 250B Series ensures it will withstand the industry's most corrosive environments.

ITC250-B — Battery Operated Level Display		
Part Number	Input	ON/OFF Switch
ITC250-B	4-20mA	Latching
ITC250-B-M	4-20mA	Momentary

Battery Replacements	
Part Number	Material
ITC250-B-LiRB	Lithium Ion


Specifications

Display	4 Digit Chameleon Color LCD (38mm x 22mm)
Displayed Values	-999 ± 9999
Power Supply	2600mAh Battery Powered
Protection Class	NEMA 4X IP67
Accuracy	0.1% @ 25°C One Digit
Operating Temperature	-20 - 158°F (-29 - 70°C)
Storage Temperature	-20 - 158°F (-29 - 70°C)
Protection Class	NEMA 4X IP67
Case	Wall Mounted Material - Polycarbonate
Dimensions (WxNxH)	110 x 105 x 67 mm



20mA Full

4mA Empty



ICON[™] Corrosion-Free
PROCESS CONTROLS Instrumentation Equipment[™]

ON/OFF
Latching Switch (std.) or
Momentary (deadman type)




Diagram showing the front view of the LevelPro 250B Battery Powered Display. The device is rectangular with a blue display screen. Dimensions are indicated: 92.15mm width, 80.15mm height, and 114.00mm total height including the mounting bracket. The display shows a battery level indicator, a QR code, and the text "LevelPro 250B — Battery Powered Display". The device is labeled "ICON Corrosion-Free Instrumentation Equipment".